

FIELDKING

Mounted Offset Disc Harrow (Hunter Series)

FEATURES

- Used in open field workings for the superficial ploughing, shattering of clods, preparation of soil for sowing, burial of organic substances & remains.
- It can be easily transported on the tyres using the hydraulic system.
- High quality boron steel disc with 48~52 HRC hardness.
- Effectively break up heavy clods because of sturdy design and weight.
- Bearing spools for better lubrication and less load on tractor.
- High quality seals are used to prevent the bearing & hub from mud & water entry.



SPECIFICATION

DESCRIPTION	FKMODHHS-22-18	FKMODHHS-22-20	FKMODHHS-22-22	FKMODHHS-22-24	FKMODHHS-22-26
FRAME (mm)	125 x 65 x 6 (Tubular Frame)				
GANG BOLT / AXLE (mm)	28 (Solid Sq. Rod)				
NO. OF DISC	18	20	22	24	26
TYPE OF DISC	Notched Disc In Front Gang & Plain Disc In Rear Gang				
DISC DIAMETER (mm)	560 x 4 T (22")				
WIDTH OF CUT (mm Approx.)	2034	2259	2484	2709	2934
DISTANCE BETWEEN DISCS (mm)	225				
BEARING HUBS	8				
WEIGHT (Kg. Approx.)	645	685	770	810	850
TRACTOR POWER (HP)	60~70	70~80	80~90	90~100	100~110


*The weight and working data contained in the present creative are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification /improvement.



Gang adjustment



Combination of plain & notched disc (Boron steel)



Adjustable scrapper



Bearing hub



Gang axle lock

**BERI UDYOG
Pvt. Ltd.**

Corporate Office:

Plot No. 235-236 & 238-240, Sec-3,
HSI IDC, Karnal- 132001 (Haryana), India
+91 184 2221571/ 72/ 73
info@fieldking.com

Sales & Marketing Office (Exports):

DGL 221, 2nd Floor, The Galleria,
Mayur Vihar, Phase-1, Delhi, India
+91 11 48042089
exports@fieldking.com